

## MA-WO52-DP7

### 4.4-6.05 GHz Dual Polarization Omni Directional Antenna

MARS 4.4-6.05 GHz Dual Polarization Omni Directional Antenna provides a cost effective solution for an extra-large scale WLL, WLAN, ISM and Point-to-Multi Point applications.

UV protected radome suitable for harsh environment installations. Antenna features stable performance with exceptional 7 dBi of gain.

**Applications:**

- MESH Networks.
- Point-to-Point Applications.



### Specifications

#### **Electrical**

Frequency Range	4.4 -6.05 GHz
GAIN, typ.	7 dBi
VSWR.	<2: 1 typ. ; 2.5: 1 max.
Polarization	Dual Pole Vertical & Horizontal
3 dB Beam-Width, Azimuth, typ.	Omni - Directional
3 dB Beam-Width, Elevation, typ.	18°
Input power, max.	10 Watt
Port to Port Isolation, typ.	35 dB
Lightning Protection	DC Grounded
Input Impedance	50 Ohm

#### **Mechanical**

Dimensions (HxDia.)	420 x 66 mm
Weight	630 gr.
Connector	2 x N-Type, Female
Radome	UV Protected Plastic
Mount	2" Pole Mount

#### **Environmental**

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com